



To: Mailmaster Letterboxes
 PO Box 1683
 Coorparoo Dc Qld 4151
mail@mailmaster.biz

Date: _____

Phone: 1300 794 5555

Fax: 07 38473188

From: _____

Email: _____

Phone: _____

Fax: _____

Delivery Address: _____

MAILMASTER Alum Series Bank Units Landscape = 240mm Deep Portrait = 330mm Deep

7	1142/967/909												
6	982/832/782												
5	822/697/656												
4	662/562/529												
3	502/427/402												
2	342/292/276												
1	183/157/149												
	Portrait	240	474	706	938	1170	1402	1634	1866	2098	2330	2562	2794
	Landscape	340	672	1004	1336	1668	2000	2332	2664	2996	3328	3660	N/A
No. of Boxes		1	2	3	4	5	6	7	8	9	10	11	12

MAILMASTER Stainless Steel Series Bank Units Landscape = 240mm Deep Portrait = 330mm

7	1142												
6	982												
5	822												
4	662												
3	502												
2	342												
1	183												
	Portrait	240	474	706	938	1170	1402	1634	1866	2098	2330	2562	2794
	Landscape	350	690	1050	1400	1750	2100	2450	2800				
No. of Boxes		1	2	3	4	5	6	7	8	9	10	11	12

Note: The above table for the stainless steel banks indicates the box size. The face plate typically overhangs the box by 25mm per side (50mm overall). This is the case for both in wall applications where the face plate acts as a flange or as surface mounted or free standing arrangements whereby the sides and back may be trimmed or shrouded with stainless steel.

Checklist

- Landscape Front Opening Key Lock Master Key In / On Wall
- Portrait Rear Opening Latch Lock Box Numbering Free Standing
- Colour: Std Powder Coat Colour Anodised Other: _____

Comments: _____

Extract from ASNS 4253-1994

A2 POSITIONING OF MAILBOXES Individual mailboxes and groups of mailboxes for residences or business premises should be located as close as possible to the footpath, driveway or roadway boundary of the property, with the aperture facing the footpath or roadway. If the property has a driveway entrance from the roadway, mailboxes should be positioned as near as practicable to the junction of the driveway and the roadway. In all cases, access to the delivery aperture should be unhindered, with the removal of rubbish and overhanging shrubs and trees. Mailboxes should be positioned so that the aperture is between 900 mm and 1200 mm above ground level and conveniently located so that the delivery officer does not have to dismount from a bicycle or motorcycle to insert mail. Groups of mailboxes for flats or apartments may be positioned at right angles to the footpath or roadway and parallel to the driveway with apertures located within the height range of 600 to 1600 mm. Mailboxes positioned in this way should commence as close to the footpath boundary as practicable, and provide adequate